

# Carisma® 3"

Linear Direct/Indirect




PROJECT:

TYPE:

## Features

Carisma® Pendant is part of a family of architectural linear luminaires that offer excellent performance, quality, visuals and value. A sleek edge-to-edge lens design results in an elegant aesthetic with clean lines. Carisma®'s patent pending design includes an integrated optical system that minimizes optical losses, allowing for industry-leading efficacy that meets the stringent requirements for DLC Listing (*DLC Listing pending*). A tailored end cap design and Amerlux's trusted catch-and-latch mechanism prevents all light leakage.

The Carisma® Pendant offers luminaires with 2" and 3" wide apertures, delivering seamless lighting as discrete individual fixtures, continuous rows or patterns. Carisma® can be specified to the nearest 1/8" and is available in pendant, surface, wall and recessed mounting options, providing designers with the versatility to light up a space with their Carisma®.



CAR3-DI

## Product Overview

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| Type:               | Direct/Indirect distribution with Pendant or Wall Mounting<br>Performance lens down/Batwing lens up |
| Wattage:            | 5W/ft, 10W/ft (or specify both direct & indirect wattage each between 3W/ft and 10W/ft)             |
| Color Temp:         | 2700K*, 3000K, 3500K, 4000K (*90+ CRI only)                                                         |
| CRI:                | 80+ typ. or 90+ typ.                                                                                |
| Dimming (wired):    | 0-10V, 1% dim (standard)<br>Lutron LDE1 Hi-lume® 1% Soft-On/Fade-to-Black<br>DALI, 1% dim           |
| Dimming (wireless): | Lutron Athena (integral wireless RF node)<br>BubblyNet Bluetooth                                    |

## Certifications



## Fixture Summary

### Performance Data

| Wattage per Foot | Delivered Lumens Direct | LPW   | Delivered Lumens Indirect | LPW   | Color Temp | CRI |
|------------------|-------------------------|-------|---------------------------|-------|------------|-----|
| 5/5              | 2632                    | 129.5 | 2624                      | 142.0 | 3500K      | 80+ |
| 10/10            | 5253                    | 123.1 | 4979                      | 135.6 | 3500K      | 80+ |

Data is based on 4' fixture with Performance Lens direct & Batwing Indirect,, 3500K-80 120V IES files available on website.

### Electrical Data

| Wattage per Foot | Voltage | 4'           |      | 8'           |      |
|------------------|---------|--------------|------|--------------|------|
|                  |         | System Watts | Amps | System Watts | Amps |
| 5/5              | 120V    | 38.3         | 0.32 | 78.4         | 0.65 |
|                  | 277V    | 37.3         | 0.15 | 78.3         | 0.30 |
| 10/10            | 120V    | 75.4         | 0.63 | 154.9        | 1.30 |
|                  | 277V    | 75.4         | 0.29 | 152.0        | 0.56 |

Electronic multi-volt (120-277VAC), constant current LED driver.

### Runs

Individual Runs: 2' - 8' (specify in 1' increments).

Continuous Runs: > 8' (specify to the nearest foot).

Custom: Made to measure lengths available (specify to nearest 1/8" of field dimensions). Requires approval drawings. Added cost & lead time.

### Standard Patterns

|     |     |     |     |     | Wall to Ceiling | Custom |
|-----|-----|-----|-----|-----|-----------------|--------|
| Yes | Yes | Yes | Yes | Yes | No              | No     |

PROJECT:

TYPE:

### Ordering Information

| CAR3-DI |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 120/277                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                |                                                                             |                                                                                                                  |   |            |    |    |        |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|---|------------|----|----|--------|
| 1       | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3                                                                                                                                                                              | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 5                                                                                                                                                                                                                          | 6                                                                                                                                                                                                                                                                                                                                                              | 7                                                                           | 8                                                                                                                | 9 | 10         | 11 | 12 |        |
| 1       | Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 2                                                                                                                                                                              | Optics (select 1 for direct & 1 for indirect)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 3                                                                                                                                                                                                                          | Mounting                                                                                                                                                                                                                                                                                                                                                       |                                                                             |                                                                                                                  |   |            |    |    |        |
|         | CAR3-DI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Direct<br>PL performance lens<br>Indirect<br>BAT batwing lens                                                                                                                  | Pendant Mount (aircraft cable suspension)<br>ASW04 through ceiling tile or gyp board, white, 4'*<br>ASW10 through ceiling tile or gyp board, white, 10'<br>ASW20 through ceiling tile or gyp board, white, 20'<br>ASB04 through ceiling tile or gyp board, black, 4'*<br>ASB10 through ceiling tile or gyp board, black, 10'<br>ASB20 through ceiling tile or gyp board, black, 20'<br>ASW04T over ceiling tee, white, 4'*<br>ASW10T over ceiling tee, white, 10'<br>ASW20T over ceiling tee, white, 20'<br>ASB04T over ceiling tee, black, 4'*<br>ASB10T over ceiling tee, black, 10'<br>ASB20T over ceiling tee, black, 20'<br>* 4' (xxx04) is standard length, other lengths are additional charge | Wall Mount<br>WM wall mount                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                |                                                                             |                                                                                                                  |   |            |    |    |        |
| 4       | Circuiting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 5                                                                                                                                                                                                                          | Wattage (per foot, direct/indirect)                                                                                                                                                                                                                                                                                                                            |                                                                             |                                                                                                                  | 6 | Color Temp |    | 7  | Finish |
|         | 1 single circuit, direct & indirect are on the same circuit<br>2 dual circuit, direct & indirect controlled independently<br>Note: 3' & below lengths must use single circuit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Standard<br>5/5<br>10/10<br>5/10<br>10/5<br>Optional<br>Specify both direct & indirect wattages, each between 3 & 10 W/ft.<br>Note: If specifying different wattage for direct & indirect, then must specify dual circuit, | 80+ CRI<br>30 3000K-80+<br>35 3500K-80+<br>40 4000K-80+                                                                                                                                                                                                                                                                                                        | 90+ CRI<br>279 2700K-90+<br>309 3000K-90+<br>359 3500K-90+<br>409 4000K-90+ | HW high reflectance matte white<br>BT black texture<br>ST silver texture<br>For other RAL color, consult factory |   |            |    |    |        |
| 8       | Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 9                                                                                                                                                                              | Length                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 10                                                                                                                                                                                                                         | Configuration                                                                                                                                                                                                                                                                                                                                                  |                                                                             |                                                                                                                  |   |            |    |    |        |
|         | 120/277                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | _____ X _____ X _____<br>Length A      Length B      Length C<br>- all patterns      - all patterns      - PU<br>- IND      - PR (2 lengths of 2')      - PZ<br>- CON<br>- CUS | IND <sup>1</sup> individual fixture, 2' to 8' in 1' increments<br>CON continuous run > than 8', specify to nearest foot<br>CUS custom made to measure lengths (specify to nearest 1/8" of field dimensions)<br>Standard Patterns (see pg 6 for details)<br>PLL L left, (2) straights + (1) 90° corner, leg right<br>PLR L right, (2) straights + (1) 90° corner, leg left<br>PU U shape, (3) straight lengths + (2) 90° corners<br>PR Rectangle shape, (4) straight lengths + (4) 90° corners<br>PZ Z shape, (3) straight lengths + (2) 90° corners                                                                                                                                                   |                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                |                                                                             |                                                                                                                  |   |            |    |    |        |
| 11      | Drivers/Controls                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                            | 12                                                                                                                                                                                                                                                                                                                                                             | Options/Accessories                                                         |                                                                                                                  |   |            |    |    |        |
|         | Wired<br>0-10V 1% electronic dimming, multi-volt, 120-277VAC<br>HILUME-H-ECO Lutron LDE1 Hi-lume® 1% dim Soft-On/Fade-to-Black<br>DALI DALI dimming 120-277VAC, 1% dim<br>Wireless<br>Awnr-WH-SR Lutron Athena wireless node, RF only, white, D4i/DALI-2<br>Awnr-BL-SR Lutron Athena wireless node, RF only, black, D4i/DALI-2<br>Awnr-WH-010 Lutron Athena wireless node, RF only, white, 0-10V<br>Awnr-BL-010 Lutron Athena wireless node, RF only, black, 0-10V<br>Awnr-OCC-WH-SR Lutron Athena wireless node, Occupancy & Daylight sensor, white, D4i/DALI-2<br>Awnr-OCC-BL-SR Lutron Athena wireless node, Occupancy & Daylight sensor, black, D4i/DALI-2<br>Awnr-OCC-WH-010 Lutron Athena wireless node, Occupancy & Daylight sensor, white, 0-10V<br>Awnr-OCC-BL-010 Lutron Athena wireless node, Occupancy & Daylight sensor, black, 0-10V<br>BN-BT-OCC-WH-SR BubblyNet Bluetooth node, Occupancy & Daylight sensor, white, D4i/DALI-2<br>BN-BT-OCC-WH-010 BubblyNet Bluetooth node, Occupancy & Daylight sensor, white, 0-10V |                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                            | EMC-PF <sup>2</sup> emergency circuit requires power feed located in last fixture section (for other locations consult factory)<br>PF <sup>2</sup> Extra power feed for additional circuiting<br>EMB* emergency battery pack (not available for lengths under 4')<br>* An additional PF needs to be ordered for all 2-circuit DI fixtures ordered with an EMB. |                                                                             |                                                                                                                  |   |            |    |    |        |

1 Lengths less than 4' may have restrictions based upon wattage, lengths, drivers or other options.  
 2 Not available with IND (individual) configuration.

### PROJECT:

### TYPE:

## Specifications

### Construction

Extruded aluminum housing and reflector. Die-cast end caps match fixture body finish.

**Weight:** 3.5 lbs/ft (may vary based on configurations and accessories)

### Optical

#### Direct:

All Direct lenses are snap-in, extruded acrylic, with a maximum length of 8'. Amerlux's proprietary acrylic lens provides excellent transmission while effectively concealing source image.

**PL** - Performance lens provides high efficiency with controlled lens surface brightness.

#### Indirect:

Extruded acrylic lens with a maximum length of 4'.

**BAT** - Batwing uplight lens spreads light directly above fixture. A minimum of 18" distance from ceiling plane and top of fixture is suggested.

### LED

Our LED binning is within 3 MacAdam ellipse. Boards are configured for maximum flexibility resulting in even illumination no matter what the fixture layout. LED boards are easily replaced in the field with just a Phillips screw driver.

**Color Temperature Options:** 2700K\*, 3000K, 3500K, 4000K

**CRI:** 80+, 90+

**R9:** 16 @ CRI 83; **R9:** >50 @ CRI 92

**Life:** 50,000+ hr., > 70% of initial lumens (L70)

**\* Available in 90+ CRI only**

### Electrical

**Wiring:** Individual and "Beginning of Run" (BOR) fixtures are prewired with power cord. All configurations have quick connect power harnesses for row connections.

- 1 - Single Circuit, direct & indirect are on the same circuit
- 2 - Dual Circuits, direct & indirect controlled independently

**Standard Wattage:** 5W/ft, 10W/ft.

**Optional Wattages:** 3W/ft, 4W/ft, 6W/ft, 7W/ft, 8W/ft, 9W/ft. (3W & 4W have a minimum length of 4'). For other wattages consult factory. Emergency circuit via remote inverter or auxiliary emergency power supply (by others).

**This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux® recommends using additional surge protection with this unit (supplied by others), surge and over voltage damage is not covered under warranty.**

**EMC-PF** - Emergency circuit requires power feed to be located in last fixture section for continuous runs. For other locations consult factory. Not available for individual (IND) configuration.

**PF** - Extra power feed for additional circuiting. Not available for individual (IND) configuration.

### Finish

All painted surfaces are premium powder coated baked on for maximum durability and color stability.

**HW** - High reflective matte White

**BT** - Black Texture

**ST** - Silver Texture

For special paint colors supply RAL and/or actual paint chip for factory consultation.

### Configurations/Lengths

#### Straights:

**IND** - Individual fixtures are made of single standard lengths of 2 ft to 8 ft (in 1' increments). These are stand alone fixtures with matching End Caps, supplied with the mounting hardware. Lengths less than 4' may have restrictions based upon wattage, lengths, drivers or other options.

**CON** - Continuous runs, > 8' specified to nearest whole foot length in 1' increments. Runs made from standard lengths have End Caps at the beginning and end of run. Runs > 60' may require second power feed. Each housing has factory installed alignment pins. Mating fixtures are easily aligned and joined. Wiring is made fast and positive with molded quick connectors.

**CUS** - Custom made to measure runs are made to nearest 1/8" of customer supplied field measurements or drawings. Custom lengths use the same hardware for hairline joining.

#### Patterns:

**PXX** - Standard Patterns consist of 90° corners with standard lengths (4' to 8' in 1' increments), continuous runs or made to measure lengths. Depending upon complexity of the pattern drawings may be required from the customer. If ordering please give overall lengths.

**A'-B'-PLL** - L Left - (1) 90° Corner (2) segments. Specify overall segments: A' & B'

**A'-B'-PLR** - L Right - (1) 90° Corner (2) segments. Specify overall segments: A' & B'

**A'-B'-PR** - Rectangle - (4) 90° Corners joining (4) segments. Specify overall segments: A' & B'

**A'-B'-C'-PU** - U shape - (2) 90° Corners joining (3) segments. Specify overall segments: A', B', & C'

**A'-B'-C'-PZ** - Z shape - (2) 90° Corners joining (3) segments. Specify overall segments: A', B', & C'

**See page 6 for layouts.**

### Mounting

The Carisma® Direct/Indirect is intended for pendant or wall mounting. For even lighting on ceiling, Amerlux suggests 18" minimum distance from top of fixture to ceiling when pendant mounted.

**Pendant Mount-ASWxx** - Direct/Indirect pendant mounted in center of ceiling tile or gypsum board ceiling (standard) i.e. ASWxx. Or if canopy is installed on a grid Tee runner add, **T** i.e. ASWxxT.

Cable is stranded stainless steel wire. All fittings are protected against rust and corrosion. Canopies are 5" x 1/4" die formed painted steel. Adjustment mechanism allows for infinite height adjustment. Amerlux recommends the required feed and non-feed suspensions based upon length and electrical options. Options include: color of canopy and power cord (black or white), length 4', 10' or 20', and mounting condition, in center of ceiling tile and in gypsum board ceiling (standard) i.e. ASWxx. Or if canopy is installed on a grid Tee runner add, **T** i.e. ASWxxT

**Wall Mount-WM** - Direct/Indirect wall mounted using steel cleat bracket attached to fixture housing and wall bracket with set screws. Two bracket assemblies are used for each length. A third center bracket may be recommended. J-box required at feed locations.

**Please note: Single Circuit is standard, the direct & indirect are on the same circuit. For Dual Circuits, direct & indirect are controlled independently.**

### Options

**EMB** - Emergency battery pack - 10W output power, 90 min of illumination time, up to 1300 lm of initial light output. Illuminated test-switch/charging indicator light is provided. Wattage consumption by EM: 2.5W/ft (4ft fixture), 1.25W/ft (8ft fixture). Request can be made to light up 4ft section on 8ft unit.

### Certifications

Approved to UL standards for damp locations as tested by CSA  
Intended for indoor use only  
DLC Listing pending

### Warranty

Amerlux's 5 year limited warranty. Please consult Amerlux website for details.



# Carisma® 3"

Linear Direct/Indirect




PROJECT:


TYPE:

## Product Details

### Pendant




### Wall Mount



## Tool-less Joining


Line up the two housings using the alignment brackets. Secure them together by using the Catch & Latch System on the top of the extrusion.



PROJECT:


TYPE:

### Cable Kit Suspension - Ceiling or Gypsum Board (ASW04, ASW10, ASW20, ASB04, ASB10, ASB20)



| Cat#   | Length | Cord/Canopy | Application         |
|--------|--------|-------------|---------------------|
| ASW04  | 4'     | white/white | ceiling tile/gypsum |
| ASW10  | 10'    | white/white | ceiling tile/gypsum |
| ASW20  | 20'    | white/white | ceiling tile/gypsum |
| ASB04  | 4'     | black/black | ceiling tile/gypsum |
| ASB10  | 10'    | black/black | ceiling tile/gypsum |
| ASB20  | 20'    | black/black | ceiling tile/gypsum |
| ASW04T | 4'     | white/white | ceiling tee         |
| ASW10T | 10'    | white/white | ceiling tee         |
| ASW20T | 20'    | white/white | ceiling tee         |
| ASB04T | 4'     | black/black | ceiling tee         |
| ASB10T | 10'    | black/black | ceiling tee         |
| ASB20T | 20'    | black/black | ceiling tee         |

### Tee Grid or Screw Slot (ASW04T, ASW10T, ASW20T, ASB04T, ASB10T, ASB20T)



PROJECT:


TYPE:

### Optional Sensor/RF Node

Amerlux® has partnered with control companies to create building environments that are safer and smarter, than ever before. At the heart of our partnership is intelligent RF nodes and Smart Sensor, the most advanced digital wireless communication and sensors available today. Integrated into Amerlux products.

Minimum run length is 3' for wireless sensor and RF node.

#### INDIVIDUAL (MIN 3' LENGTH)





### Carisma® 2" Patterns

#### Standard Patterns

All corners are standard 90°, standard length legs.

Use standard lengths: 4' min to 8' in 1 foot increments.

Continuous runs must be the same length in pairs for closed configuration.



**PLL** - L Left, (2) straights + (1) 90° corner, leg right

**PLR** - L Right, (2) straights + (1) 90° corner, leg left

Provide overall lengths: A' & B'


Nomenclature: A-B-PLL A-B-PLR



**PR** - Closed Rectangle, (4) straight lengths + (4) 90° corners

Provide overall lengths: A' & B'


Nomenclature: A-B-PR



**PU** - Open U, (3) straight lengths + (2) 90° corners

Provide overall lengths: A', B' & C'

Nomenclature: A-B-C-PU



**PZ** - Open Z, (3) straight lengths + (2) 90° corners

Provide overall lengths: A', B' & C'

Nomenclature: A-B-C-PZ

PROJECT:

TYPE:

### Performance Data

**Multiplying Factors:** (Multiplying Factor is based on 3500K-80 120V IES file on website)


| Wattage: | 3W   | 4W   | 5W   | 6W   | 7W   | 8W   | 9W   | 10W |
|----------|------|------|------|------|------|------|------|-----|
| Factor:  | 0.30 | 0.39 | 0.51 | 0.61 | 0.71 | 0.81 | 0.90 | 1.0 |

| CCT:    | 3000K-80 | 3500K-80 | 4000K-80 | 2700K-90 | 3000K-90 | 3500K-90 | 4000K-90 |
|---------|----------|----------|----------|----------|----------|----------|----------|
| Factor: | 0.97     | 1.0      | 1.02     | 0.93     | 0.98     | 0.98     | 1.02     |

#### DIRECT

| Performance Lens   |                   |               |     |
|--------------------|-------------------|---------------|-----|
| Ordered Wattage/Ft | Tested Wattage/Ft | Lumens per Ft | LPW |
| 3                  | 3.02              | 388           | 129 |
| 4                  | 3.95              | 513           | 130 |
| 5                  | 5.08              | 658           | 130 |
| 6                  | 6.00              | 790           | 132 |
| 7                  | 6.98              | 921           | 132 |
| 8                  | 8.00              | 1053          | 132 |
| 9                  | 9.00              | 1178          | 131 |
| 10                 | 10.66             | 1313          | 123 |


Data is based on 3500K, 80 CRI



#### INDIRECT

| Batwing Lens       |                   |               |     |
|--------------------|-------------------|---------------|-----|
| Ordered Wattage/Ft | Tested Wattage/Ft | Lumens per Ft | LPW |
| 3                  | 2.60              | 387           | 149 |
| 4                  | 3.48              | 512           | 147 |
| 5                  | 4.62              | 656           | 142 |
| 6                  | 5.20              | 787           | 151 |
| 7                  | 6.01              | 918           | 153 |
| 8                  | 6.98              | 1050          | 150 |
| 9                  | 7.85              | 1174          | 150 |
| 10                 | 9.18              | 1245          | 136 |

Data is based on 3500K, 80 CRI



PROJECT:

TYPE:

### Dimming Compatibility

Amerlux® Carisma® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (*Dimmer, Fixture Quantity, Voltage, etc*) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---


#### 0-10V - DIMMING (Standard)

Integrates into a variety of building management and daylighting controls

##### Notes:

- 120V or 277V\*
- Dims down to 1% light output
- Requires interface to turn off power to driver
- Consult Dimming manufacturer for installation instructions - **DO NOT SHARE NEUTRALS!**

#### 0-10V Wiring Diagram



#### Compatible Dimmers\*:

| Wall Box          |              |           | Central System                            |
|-------------------|--------------|-----------|-------------------------------------------|
| Lutron:           | Wattstopper: | Leviton:  | Lutron Grafikx Eye with GRX-TV1 Interface |
| Diva - DVSTV      | ADF-120277   | Renoir II |                                           |
| Maestro - MS-Z101 |              |           |                                           |
| Nova-T - NTSTV-DV |              |           |                                           |

#### LUTRON LDE1 DIMMING

Integrates into Lutron EcoSystem building management


##### Notes:

- 120VAC or 277VAC\*
- Dims down to 1% Soft-On/Fade-to-Black
- EcoSystem Control
- Consult Dimming manufacturer for installation instructions - **DO NOT SHARE NEUTRALS!**

#### Compatible Dimmers\*:

| Lutron ECO System       | Central System                       |
|-------------------------|--------------------------------------|
| Pow Pak Dimming Modules | Lutron EcoSystem compatible controls |
| Energi Savr Node        |                                      |
| Grafik Eye QS/Homeworks |                                      |
| QS Control Unit         |                                      |
| Quantum Hub             |                                      |
| Homeworks QS/My Room    |                                      |

#### LDE1 (HILUME-H-ECO) EcoSystem Digital Control Wiring Diagram



##### Notes:

\* Driver is 277VAC dimmable with appropriate dimmer (*by others*). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.

\* The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.

# Carisma® 3"

Linear Direct/Indirect



PROJECT:

TYPE:

## Dimming Compatibility (continued)

Amerlux® Carisma® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (*Dimmer, Fixture Quantity, Voltage, etc*) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---

### DALI - DALI DIMMING 120V-277V

Digital control protocol allows individual fixture control


#### Notes:

- 120VAC - 277VAC\*
- Dims down to 1% light output in most cases

#### Compatible Dimmers\*:

| Wall Box                 | Central System |
|--------------------------|----------------|
| Leviton CD250 Controller | Dynalite       |
|                          | Fifth Light    |


#### DALI Wiring Diagram



## Emergency Fixture with Built-In Battery Pack

Emergency fixture with built-in battery pack (**EMB**) wiring:

Note: EMB not available on lengths under 4'.



#### Notes:

\* Driver is 277VAC dimmable with appropriate dimmer (*by others*). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.

\* The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.